


Islandaire EZ Series NR is a replacement for the Nesbitt Modular RoomMate. Our commercial duty construction with heavy-gauge, galvanized steel and superior components create an efficient, reliable unit. This design eliminates the need for any interior or exterior renovation. Use of the existing wall sleeve-cabinet and louver saves time and money, two very important factors in today's competitive environment!



### FEATURES

- Proudly Assembled in the U.S.A.
- ETL listed products
- Superior Energy Efficiency Ratios (EERs)
- Commercial Duty Construction with Heavy Gauge Galvanized Steel
- Designed for exact replacement of existing sleeve opening
- Energy Efficient Rotary Compressors
- P.S.C. Evaporator and Condenser Motors
- High-Efficiency Refrigeration Coils Used to Provide Superior Heat Transfer
- Units Available as Cooling only, Cooling with Electric Heat, Cooling with Hydronic Heat, or Heat Pumps
- Custom Options Available
- Available with wired and wireless wall thermostats
- NYC MEA Number 358-93-E Vol. II



\*Specifications are subject to change due to ongoing product development.



## MODELS

	EZ09			EZ12			EZ15	
<b>VOLTS</b>	115	208 / 230	277	115	208 / 230	277	208 / 230	277
<b>BTUH COOL</b>	9,200	9,200	9,400	11,800	12,000	11,500	14,500	14,500
<b>AMPS</b>	8.87	4.86 / 4.39	3.77	12.22	6.08 / 5.5	4.89	8.73 / 7.89	6.62
<b>WATTS COOL</b>	1,020	1,010	1,045	1,405	1,265	1,355	1,815	1,835
<b>EER</b>	9.0	9.1	9.0	8.4	9.5	8.5	8.0	7.9
<b>CFM HIGH</b>	400	400	400	420	420	420	500	500
<b>CFM LOW</b>	260	260	260	350	350	350	400	400
<b>BTUH HEATING</b>	9,000	8,800	9,000	11,500	11,000	11,500	13,500	13,500
<b>WATTS HEATING</b>	975	955	975	1295	1150	1205	1520	1520
<b>C.O.P.</b>	2.7	2.7	2.7	2.6	2.8	2.8	2.6	2.6
<b>WEIGHT (LBS)</b>	110	110	110	115	115	115	120	120

\*CFM values are dry coil (not in cooling mode).




Where applicable, cooling capacities are specified at conditions of 95 °F DB/75 °F WB (35 °C DB/24 °C WB) outdoor and 80 °F DB/67 °F WB (27 °C DB/19 °C WB) indoor and heating capacities are specified at conditions of 47 °F DB/43 °F WB (8 °C DB/6 °C WB) outdoor and 70 °F DB/60 °F WB (21 °C DB/16 °C WB) indoor in accordance with AHRI 310/380 and CSA C744 standards. Wattage, Amperage, EER, and COP listings include compressor, evaporator motor and condenser fan motor. The above ratings are a typical heat pump style unit.

Heating Option	Voltage (1)	Wattage	BTU/h	Amps (2)
B	208	2,045	7,000	9.83
	230	2,500	8,500	10.87
	277	2,500	8,500	9.03
C	208	2,780	9,500	13.37
	230	3,400	11,600	14.78
	277	3,400	11,600	12.27
D	208	3,435	11,700	16.51
	230	4,200	14,300	18.26
	277	4,200	14,300	15.16
E	208	4,090	14,000	19.66
	230	5,000	17,100	21.74
	277	5,000	17,100	18.05

(1) Voltage is Single Phase, Alternating Current and R.M.S.

(2) Amp values are for heating element only.

Line Voltage	Maximum Amperage	Wall Socket Configuration	Receptacle Number	Electrical Heat Options
115	12		NEMA 5-15R	1.3
115	16		NEMA 5-20R	1.7
208/230	12		NEMA 6-15R	2.5
208/230	16		NEMA 6-20R	3.6
208/230	24		NEMA 6-30R	4.2 - 5.0
277	16		NEMA 7-20R	2.5 - 4.2
277	24		NEMA 7-30R	5.0



Ask your salesman about  
our DR. PTAC option!\*




\*100% conditioned  
fresh air

## EZ Series VH Unit Available

Vertical Water Source Hybrid Heat  
Pump, Replacement For:

CGC InnKeeper/HomeKeeper



Scan for more information

500 Middle Country Road, St. James, NY 11780 • 1-800-886-2759  
e-mail: [sales@islandaire.com](mailto:sales@islandaire.com) • [www.islandaire.com](http://www.islandaire.com)  
Ph: 631-471-2900 • Fax: 631-471-2913



Locally Represented By: