

Islandaire EZKF Series KF is a replacement for the Remington, Singer and McQuay models of K units. Our commercial duty construction with heavy gauge galvanized steel and superior components create an efficient, reliable unit. This design eliminates the need for any interior or exterior renovation. Use of the existing wall sleeve-cabinet and louver saves time and money, two very important factors in today's competitive environment! If the need does occur where the wall sleeve, sloped room cabinet and flat top room cabinet and/or louver needs to be replaced, we manufacture these accessories as well. If cooling section only is ordered a mox plug is provided.

FEATURES

- Proudly Designed and Engineered in the U.S.A.
- ETL listed products
- Superior Energy Efficiency Ratios (EERs) and Coefficient of Performance (COPs)
- Commercial Duty Construction with heavy gauge, painted galvanized steel, extensive rust prevention features
- Designed for exact replacement of existing sleeve opening
- Energy Efficient Rotary Compressors
- BLDC Condenser Motor
- High-Efficiency Refrigeration Coils Used to Provide Superior Heat Transfer
- Units Available as Cooling only, Cooling with Electric Heat, Cooling with Hydronic Heat, or Heat Pump
- Available with wired and wireless wall thermostats
- NYC MEA Number 358-93-E Vol. II
- High-Efficiency, energy-conserving design
- Dual Condensate Drains
- Custom Options Available
- Thermostatic Dump Valve as standard feature
- Remote Thermostat Capable (Standard)



Voltage/Line Cord	
1 - 115v, 20 Amps	5 - 115v, 15 Amps
2 - 208/230v, 20 Amps	6 - 115v, Hard Wire
3 - 208/230v, 30 Amps	8 - 277v, Hard Wire
4 - 208/230v, Hard Wire	9 - 208/230v, 15 Amps

Cooling Capacity
09 - 9,500 BTU
12 - 12,000 BTU
16 - 15,000 BTU

Model Type
KF - Remington, Singer, McQuay

Return/Discharge Options
4 - Front/Bottom Ret./Top Dis.

Functional Options	Functional Option Codes*
B - Motorized Fresh Air Damper	B - B
D - Indoor Freeze Protect	L - BD
	2 - D

*Codes are entered into model number.

Component
EZ - Cooling Chassis

System Type
K - Std. Chassis R32
L - Heat Pump R32

Identity Code
0 - Special
6 - Standard

EZ KF 12 L 2 C 1 S 4 6 A L

Heating Options*
A - None Cooling Only
B - 2.5 kW Elec. Heat (208v - 277v)
C - 3.4 kW Elec. Heat (208v - 277v)
D - 4.2 kW Elec. Heat (208v - 277v)
E - 5.0 kW Elec. Heat (208v - 277v)
F - Hyd. Fan Cycle W/T-Stat (115v - 277v)
G - Hyd. With Aquastat (115v - 277v)
H - Hyd. W/2.5 kW B.U. Heat (208v - 277v)
I - Hyd. W/3.6 kW B.U. Heat (208v - 277v)
Y - 1.3 kW Elec. Heat (115v Only)
Z - Hyd. W/1.3 kW B.U. Heat (115v Only)

* Options D & E only available on 12kBTU and 16kBTU units
Option E only available on 15kBTU unit

Hydronic Options
I - None
A - Line Volt NO/NC Switch
B - 24v NO/NC Switch

Power Mgt. Options	Power Mgt. Codes*
A - None	A- A
C - Energy Mgt. N/O	P- C
D - Energy Mgt. N/C	T- D



*Codes are entered into model number.

Room Controls
E - Wireless Thermostat (specify type when ordering)
K - None
N - Wall Thermostat Interface, Std. Elect. Cntrls
S - Std. Electronic Controls (Unit Mounted)



*Specifications are subject to change due to ongoing product development.

6140638 Rev. A (03/02/26)





EZKF Documentation List:

P/N	Document Title
6140500	Instructions, External Drain Kit
6140501	Instructions, Internal Drain Kit
6140642	Manual, EZKF, Installation/Owners
6140643	Manual, EZKF Engineering
6140517	Chart, EZKF Hydronic Coil Performance

MODELS								
	EZ09			EZ12			EZ16	
VOLTS	115	208 / 230	277	115	208 / 230	277	208 / 230	277
BTUH COOL	9,000	8,600 / 9,000	9,000	12,000	11,800 / 12,000	12,000	14,400 / 15,000	15,000
AMPS COOL	6.9	3.65 / 3.46	3.00	4.28	5.3 / 4.9	4.28	7.04 / 6.65	5.77
WATTS COOL	795	760 / 795	795	1,135	1,110 / 1,135	1,135	1,465 / 1,530	1,530
EER	11.3	11.3 / 11.3	11.3	10.6	10.5 / 10.6	10.6	9.8 / 9.8	9.8
CFM HIGH	440	390 / 440	440	485	440 / 485	485	530 / 560	560
CFM LOW	390	340 / 390	390	440	390 / 440	440	440 / 485	485
BTUH HEATING	8,800	8,500 / 8,800	8,800	11,800	11,600 / 11,800	11,800	13,000 / 13,500	13,500
WATTS HEATING	785	800 / 785	785	1,080	1,060 / 1,080	1,080	1,270 / 1,315	1,315
C.O.P.	3.28	3.28 / 3.28	3.28	3.2	3.2 / 3.2	3.2	3.0 / 3.0	3.0
NOISE, INDOOR LOW/ HIGH (dBA)	47/49	47/49	47/49	48/50	48/50	48/50	50/54	50/54
NOISE, OUTDOOR (dBA)	63	63	63	63	63	63	63	63
WEIGHT (LBS)	94.8	94.8	94.8	99.2	99.2	99.2	102	102

Heating Option	Voltage (1)	Wattage	BTU/h	Amps (2)
B & H	208	2,045	7,000	9.83
	230	2,500	8,500	10.87
	277	2,500	8,500	9.03
C & I	208	2,780	9,500	13.37
	230	3,400	11,600	14.78
	277	3,400	11,600	12.27
D	208	3,435	11,700	16.51
	230	4,200	14,300	18.26
	277	4,200	14,300	15.16
E	208	4,090	14,000	19.66
	230	5,000	17,100	21.74
	277	5,000	17,100	18.05
Y	115	1,300	4,400	11.30
Z	115	1,300	4,400	11.30

(1) Voltage is Single Phase, Alternating Current and R.M.S.

(2) Amp values are for heating element only.

Where applicable, cooling capacities are specified at conditions of 95 °F DB/75 °F WB (35 °C DB/24 °C WB) outdoor and 80 °F DB/67 °F WB (27 °C DB/19 °C WB) indoor and heating capacities are specified at conditions of 47 °F DB/43 °F WB (8 °C DB/6 °C WB) outdoor and 70 °F DB/60 °F WB (21 °C DB/16 °C WB) indoor in accordance with AHRI 310/380 and CSA C744 standards. Wattage, Amperage, EER, and COP listings include compressor, evaporator motor and condenser fan motor. The above ratings are a typical heat pump style unit.

Line Voltage	Maximum Amperage	Wall Socket Configuration	Receptacle Number	Electrical Heat Options
115	12		NEMA 5-15R	1.3
115	16		NEMA 5-20R	1.7
208/230	12		NEMA 6-15R	2.5
208/230	16		NEMA 6-20R	3.6
208/230	24		NEMA 6-30R	4.2 - 5.0
277	16		NEMA 7-20R	2.5 - 4.2
277	24		NEMA 7-30R	5.0

*Specifications are subject to change due to ongoing product development.



ENCLOSURES

PART NUMBER	DESCRIPTION	APPROX WT.	DIMENSIONS		
			DEPTH	WIDTH	HEIGHT
4080145-00	EZKF Enclosure Assembly	40 lbs.	7.500"	48.000"	21.000"
4084029-00	EZKF Enclosure Assembly	40 lbs.	8.500"	48.000"	21.00
Consult Factory	EZKF Enclosure Assembly, Custom colors and sizes are available	-	various	various	various




WALL SLEEVES/CABINETS

PART NUMBER	DESCRIPTION	APPROX WT.	DIMENSIONS		
			DEPTH	WIDTH	HEIGHT
2400778-06	EZKF Wall Sleeve Assembly	30 lbs.	10.500"	36.125"	24.590"
2400031-06	EZKF Wall Sleeve Assembly	30 lbs.	11.500"	36.125"	24.590"
2400625-06	EZKF Wall Sleeve Assembly	30 lbs.	12.000"	36.125"	24.590"
2401083-06	EZKF Wall Sleeve Assembly	30 lbs.	14.000"	36.125"	24.590"
2401439-06	EZKF Wall Sleeve Assembly	30 lbs.	16.000"	36.125"	24.590"




HYDRONIC OPTIONS

PART NUMBER	DESCRIPTION	APPROX WT.	DIMENSIONS		
			DEPTH	WIDTH	HEIGHT
6030584	EZKF Hydronic Coil, Opp. End	20 lbs.	1.250"	39.943"	4.500"
6030585	EZKF Hydronic Coil, Same End	20 lbs.	1.250"	39.943"	4.500"
Consult Factory	Motorized Valves - Various voltages, normally open or normally closed, sweat or threaded	-	N/A	N/A	N/A



LOUVERS/GRILLES

PART NUMBER	DESCRIPTION	APPROX WT.	DIMENSIONS		
			DEPTH	WIDTH	HEIGHT
6070034	EZKF Exterior Architectural Louver, Standard	10 lbs.	1.117"	36.000"	13.000"
4090345	EZKF Louver Hardware Kit	1 lb.	N/A	N/A	N/A



HARDWIRE KITS

PART NUMBER	DESCRIPTION	APPROX WT.	DIMENSIONS		
			DEPTH	WIDTH	HEIGHT
4092552	EZKF Hardwire Kit, 48", 115/277V	2 lbs.	N/A	N/A	N/A
4092539	EZKF Hardwire Kit, 48", 208/230V	2 lbs.	N/A	N/A	N/A



THERMOSTATS

PART NUMBER	DESCRIPTION	APPROX WT.	FEATURES		
			CONNECTION	STAGE	DISPLAY
6041206	Islandaire Non-Programmable, 2 Fan Speed	1.0 lbs.	Wireless	Single	Horizontal
6041210	Islandaire Programmable, 2 Fan Speed	1.0 lbs.	Wireless	Single	Horizontal
6041228	Islandaire Programmable (7 Day/5-1-1 Day/ Non-Programmable), Two Fan Speed	1.0 lbs.	Wired	Single	Horizontal
6041373	Islandaire Wireless, WiFi Programmable	1.0 lbs.	Wireless	Single	Horizontal
6041374	Islandaire Wireless, WiFi (Receiver Only)	1.0 lbs.	N/A	N/A	N/A
6041375	Wet Switch Kit for 6041373 Thermostat	1.0 lbs.	N/A	N/A	N/A




FILTERS

PART NUMBER	DESCRIPTION	APPROX WT.	FEATURES
6080158	EZKF Standard Filter, 30.75" L x 8.50"W x 0.25"D	2 lbs.	-



DRAIN KITS

PART NUMBER	DESCRIPTION	APPROX WT.	DIMENSIONS		
			DEPTH	WIDTH	HEIGHT
4092505	EZKF External Drain Kit	2 lbs.	N/A	N/A	N/A
4092509	EZKF Internal Drain Kit	2 lbs.	N/A	N/A	N/A



Ask your salesman about
our DR. PTAC option!*




*100% conditioned
fresh air

EZ Series VH Unit Available

Vertical Water Source Hybrid Heat
Pump, Replacement For:

CGC InnKeeper/HomeKeeper



Scan for more information

500 Middle Country Road, St. James, NY 11780 • 1-800-886-2759
e-mail: sales@islandaire.com • www.islandaire.com
Ph: 631-471-2900 • Fax: 631-471-2913



Locally Represented By: