

Islandaire EZ Series NE is a replacement for the McQuay N Series units, the sloped top style replaces the McQuay Suite and MQS Series units. Our commercial duty construction with heavy gauge galvanized steel and superior components create an efficient, reliable unit. This design eliminates the need for any interior or exterior renovation. Use of the existing wall sleeve-cabinet and louver saves time and money, two very important factors in today's competitive environment! If the need does occur where the wall sleeve-cabinet and/or louver needs to be replaced, we manufacture these accessories as well. Flat Top units are provided with the enclosure top only; Sloped units are provided with complete enclosure (top, front panel and sides).



FEATURES

- Proudly Assembled in the U.S.A.
- ETL listed products
- Superior Energy Efficiency Ratios (EERs)
- Commercial Duty Construction with Heavy Gauge Galvanized Steel
- Designed for exact replacement of existing sleeve opening
- Energy Efficient Rotary Compressors
- BLDC Evaporator and Condenser Motors
- High-Efficiency Refrigeration Coils Used to Provide Superior Heat Transfer
- Units Available as Cooling only, Cooling with Electric Heat, Cooling with Hydronic Heat, or Heat Pumps
- Custom Options Available
- Available with wired and wireless wall thermostats
- NYC MEA Number 358-93-E Vol. II

Voltage/Line Cord

- | | |
|-------------------------|-----------------------|
| 1 - 115v, 20 Amps | 6 - 115v, Hard Wire |
| 2 - 208/230v, 20 Amps | 7 - 277v, 20 Amps |
| 3 - 208/230v, 30 Amps | 8 - 277v, Hard Wire |
| 4 - 208/230v, Hard Wire | 9 - 208/230v, 15 Amps |
| 5 - 115v, 15 Amps | |

Cooling Capacity

- 07 - 7,500 BTU
- 09 - 9,500 BTU
- 12 - 12,000 BTU
- 15 - 15,000 BTU

Return/Discharge Options

- 1 - Bot. Ret./Top Dis.
- 3 - Bot. Ret./Ducted Top Dis.
- 4 - Front Ret./Top Dis.
- 6 - Front Ret./Ducted Top Dis.
- 7 - Sloped Top (Restricted)

Functional Options

- A - None
- B - Motorized Fresh Air Damper
- C - Fan Cycle Switch
- D - Indoor Freeze Protect
- E - Winter Operation

Functional Option Codes*

- | | |
|----------|---------|
| A - A | Q - BE |
| B - B | T - C |
| C - BC | U - CD |
| D - BCD | V - CDE |
| E - BCDE | Y - CE |
| H - BCE | 2 - D |
| L - BD | 3 - DE |
| M - BDE | 6 - E |

*Codes are entered into model number.

Component

EZ - Cooling Chassis

System Type

- K - Std. Chassis R32
- L - Heat Pump R32

Model Type

NE - McQuay N

Identity Code

- 0 - Special
- 5 - Standard

EZ 12 L 2 NE A 1 S 1 5 A A

Heating Options

- A - None Cooling Only
- B - 2.5 kW Elec. Heat (208v - 277v)
- C - 3.6 kW Elec. Heat (208v - 277v)
- D - 4.2 kW Elec. Heat (208v - 277v)
- E - 5.0 kW Elec. Heat (208v - 277v)
- F - Hyd. Fan Cycle W/T-Stat (115v - 277v)
- G - Hyd. With Aquastat (115v - 277v)
- H - Hyd. W/2.5 kW B.U. Heat (208v - 277v)
- I - Hyd. W/3.4 kW Dual Stage (208v - 277v)
- Z - Hyd. W/1.3 kW B.U. Heat (115v Only)

Hydronic Options

- 1 - None
- 2 - 24v NC Valve
- 3 - 115v NC Valve
- 4 - 230v NC Valve
- 5 - 277v NC Valve
- 6 - 24v NO Valve
- 7 - 115v NO Valve
- 8 - 230v NO Valve
- 9 - 277v NO Valve
- A - Line Volt NO/NC Switch
- B - 24v NO/NC Switch

Room Controls

- E - Wireless Thermostat (specify type when ordering)
- F - Wall Thermostat Interface, Master
- G - Wall Thermostat Interface, Slave
- K - None
- N - Wall Thermostat Interface, Std. Elect. Cntrls
- S - Std. Electronic Controls (Unit Mounted)

Power Mgt. Options

- A - None
- B - Power Disconnect
- C - Energy Mgt. N/O
- D - Energy Mgt. N/C
- E - Emerg. Power 115v
- F - Emerg. Power 230v
- G - Emerg. Power 277v

*Codes are entered into model number.

Power Mgt. Codes*

- | | |
|---------|--------|
| A - A | N - BG |
| B - B | P - C |
| C - BC | Q - CE |
| D - BCD | R - CF |
| E - BCF | S - CG |
| F - BCG | T - D |
| G - BD | U - DE |
| H - BDE | V - DF |
| J - BDF | W - DG |
| K - BDG | X - E |
| L - BE | Y - F |
| M - BF | Z - G |

*Specifications are subject to change due to ongoing product development.

6140600 Rev. A, ECN 10063



MODELS

	EZ07			EZ09			EZ12			EZ15	
VOLTS	115	208 / 230	277	115	208 / 230	277	115	208 / 230	277	208 / 230	277
BTUH COOL	7,000	6,800 / 7,000	7,000	9,000	9,300 / 9,500	9,000	12,000	11,800 / 12,000	12,000	14,300 / 14,500	15,000
AMPS COOL	5.13	2.74 / 2.57	2.13	6.87	3.99 / 3.70	2.87	9.96	5.43 / 5.02	4.17	7.09 / 6.54	5.70
WATTS COOL	590	570 / 590	590	790	830 / 850	795	1,145	1,130 / 1,155	1,155	1,475 / 1,505	1,580
EER	11.9	11.9 / 11.8	11.9	11.4	11.2 / 11.2	11.3	10.5	10.5 / 10.4	10.4	9.7 / 9.7	9.5
CFM HIGH *	350	350 / 350	350	350	350 / 350	350	400	400 / 400	400	450 / 450	450
CFM LOW *	280	280 / 280	280	280	280 / 280	280	350	350 / 350	350	400 / 400	400
BTUH HEAT	6,400	6,100 / 6,400	6,000	8,500	8,300 / 8,500	8,000	11,000	10,800 / 11,000	11,000	13,200 / 13,600	14,000
WATTS HEAT	570	540 / 435	535	710	745 / 585	715	920	1,010 / 780	1,030	1,285 / 1,335	1,380
C.O.P.	3.3	3.3 / 4.3	3.3	3.5	3.3 / 4.3	3.3	3.5	3.1 / 4.1	3.1	3.0 / 3.0	3.0
WEIGHT (LB.)	108	109	109	115	110	115	117	118	118	130	130

* CFM values are dry coil (not in cooling mode).

Heating Option	Voltage (1)	Wattage	BTU/h	Amps (2)
B	208	2,045	7,000	9.83
	230	2,500	8,500	10.87
	277	2,500	8,500	9.03
C	208	2,945	10,100	14.16
	230	3,600	12,300	15.65
	277	3,600	12,300	13.00
D	208	3,435	11,700	16.51
	230	4,200	14,300	18.26
	277	4,200	14,300	15.16
E	208	4,090	14,000	19.66
	230	5,000	17,100	21.74
	277	5,000	17,100	18.05
H	208	2,045	7,000	9.83
	230	2,500	8,500	10.87
	277	2,500	8,500	9.03
I	208	2,780	9,500	13.37
	230	3,400	11,600	14.78
	277	3,400	11,600	12.27
Z	115	1,300	4,400	11.30


Where applicable, cooling capacities are specified at conditions of 95 °F DB/75 °F WB (35 °C DB/24 °C WB) outdoor and 80 °F DB/67 °F WB (27 °C DB/19 °C WB) indoor and heating capacities are specified at conditions of 47 °F DB/43 °F WB (8 °C DB/6 °C WB) outdoor and 70 °F DB/60 °F WB (21 °C DB/16 °C WB) indoor in accordance with AHRI 310/380 and CSA C744 standards. Wattage, Amperage, EER, and COP listings include compressor, evaporator motor and condenser fan motor. The above ratings are a typical heat pump style unit.

DIMENSIONS

	A	B	C	D	E	F
FLAT TOP	13.250	39.753	14.187	-	7.250	41.813
SLOPED	13.250	39.753	14.187	16.000	7.471	42.375

(1) Voltage is Single Phase, Alternating Current and R.M.S.


(2) Amp values are for heating element only.



Line Voltage	Maximum Amperage	Wall Socket Configuration	Receptacle Number	Electrical Heat Options
115	12		NEMA 5-15R	1.3
115	16		NEMA 5-20R	1.7
208/230	12		NEMA 6-15R	2.5
208/230	16		NEMA 6-20R	3.6
208/230	24		NEMA 6-30R	4.2 - 5.0
277	16		NEMA 7-20R	2.5 - 4.2
277	24		NEMA 7-30R	5.0

ENCLOSURES

PART NUMBER	DESCRIPTION	APPROX WT.	DIMENSIONS		
			DEPTH	WIDTH	HEIGHT
4080661	EZNE Front Panel , Flat Top Units	10 lbs.	8.000"	43.312"	16.187"
4080385	EZNE Enclosure Assembly, Sloped w/Door	20 lbs.	7.471"	42.375"	16.000"
4081400	EZNE Duct Extension Assembly, Flat Top Units	8 lbs.	6.634"	36.000"	4.068"
4081388	EZNE Duct Assembly , Flat Top Units	13 lbs.	6.750"	41.830"	3.500"




WALL SLEEVES

PART NUMBER	DESCRIPTION	APPROX WT.	DIMENSIONS		
			DEPTH	WIDTH	HEIGHT
2400405-00	EZNE Wall Sleeve Assembly, Standard	34 lbs.	15.00"	42.00"	16.00"
2401135-00	EZNE Wall Sleeve Assembly, Break Down	33 lbs.	13.75"	42.00"	16.00"
4090339-00	EZNE Wall Sleeve Extension Kit	5 lbs.	2.000"	42.00"	16.00"




HYDRONIC OPTIONS

PART NUMBER	DESCRIPTION	APPROX WT.	DIMENSIONS		
			DEPTH	WIDTH	HEIGHT
6030153	EZNE (Flat Top) Hydronic Coil, Top Mounted	2 lbs.	1.080"	30.000"	5.000"
6030280	EZNE (Flat Top and Sloped) Hydronic Coil Assembly, Bottom Mounted	10 lbs.	1.080"	30.000"	5.000"



LOUVERS/GRILLES

PART NUMBER	DESCRIPTION	APPROX WT.	DIMENSIONS		
			DEPTH	WIDTH	HEIGHT
6070422	EZNE Exterior Louver, 42 x 16	5 lbs.	1.125"	42.000"	16.000"



THERMOSTATS

PART NUMBER	DESCRIPTION	APPROX WT.	FEATURES		
			CONNECTION	STAGE	DISPLAY
6041206	Islandaire Non-Programmable, 2 Fan Speed	1.0 lbs.	Wireless	Single	Horizontal
6041210	Islandaire Programmable , 2 Fan Speed	1.0 lbs.	Wireless	Single	Horizontal
6041228	Islandaire Programmable (7 Day/5-1-1 Day/ Non-Programmable), Two Fan Speed	1.0 lbs.	Wired	Single	Horizontal
6041373	Islandaire Wireless, WiFi Programmable	1.0 lbs.	Wireless	Single	Horizontal
6041374	Islandaire Wireless, WiFi (Receiver Only)	1.0 lbs.	N/A	N/A	N/A
6041375	Wet Switch Kit for 6041373 Thermostat	1.0 lbs.	N/A	N/A	N/A




OTHER OPTIONS

PART NUMBER	DESCRIPTION	APPROX WT.	FEATURES
4090661	External/Internal Drain Kit	1.0 lb.	-



FILTERS

PART NUMBER	DESCRIPTION	APPROX WT.	FEATURES
6080015	EZNE Standard Filter, 30.75" L x 7.00" W x 0.25"D	2 lbs.	-



**Ask your salesman about
our DR. PTAC option!***




*100% conditioned
fresh air

EZ Series VH Unit Available

Vertical Water Source Hybrid Heat
Pump, Replacement For:

CGC InnKeeper/HomeKeeper



Scan for more information

500 Middle Country Road, St. James, NY 11780 • 1-800-886-2759
e-mail: sales@islandaire.com • www.islandaire.com
Ph: 631-471-2900 • Fax: 631-471-2913



Locally Represented By: